





CYBERLITE™

LED BATTEN SHATTERPROOF SERIES - GEN 2 22W & 45W

The new Ø90mm Cyberlite batten has been designed to withstand rigorous cleaning regimes in harsh and demanding manufacturing environments. With an IP69K rating, chemical-resistant shell and all food-grade fittings, it is also compliant in HACCP-accredited facilities. Available in different wattages, lengths, lens optics, mounting options and even emergency-powered, there is a version to suit many situations in many industries! Designed and Made in Australia!



FOOD & BEVERAGE LIGHTING



PRODUCT NAME	CYBERLITE™ LED BATTEN LIGHT SERIES - GEN 2	
MODEL (GEN2)	22W	45W
PART NUMBER (STANDARD*)	CHH2250-905	CHH4550-910
POWER CONSUMPTION	22W	45W
LIGHT OUTPUT EFFECTIVE	3,916 lm	8,010 lm
LED EFFICACY	178 lm/W	
IP RATING	IP69K	
OPERATING TEMP °C	-40°C to +50°C*	
NOMINAL VOLTAGE	230V/AC	
VOLTAGE RANGE	180-265V/AC	90-305V/AC
POWER FACTOR	>0.95	
FREQUENCY RANGE	47-63Hz	
THERMAL MANAGEMENT	Active/Continuous	
CRI	Typical 80 CRI**	
CCT/KELVIN	4000K & 5000K***	
MOUNTING OPTIONS	Mounting Clips (std) Extrusion Mount, Heavy-Duty Clamps	
LED BIN SELECTION	3 SCDM Ellipses	
CONTROL OPTIONS	Non-Dimmable Std, Dimmable, DALI, Emergency Maintained, Emergency Non-Maintained	
LINE CURRENT (230V/AC)	0.45A	0.93A
DRIVER	Internal	
LENS	Chemical Resistant Polycarbonate - Diffused/Clear	
EXPECTED LIFESPAN	50,000 hours to 70% Brightness	
NET WEIGHT	3kg	3.8kg
LIGHT DIMENSIONS	90x470mm	90x940mm
WARRANTY	5 YEARS	

Find out more at dura-vision.com.au or call 1800 66 55 66

*-45°C Available on special request. **90 CRI also available ***5000K Standard CCT (Kelvin). All information subject to change without notice. V01.06.24



CYBERLITE™

LED BATTEN SHATTERPROOF SERIES - GEN 2 22W & 45W



FOOD & BEVERAGE LIGHTING

DESIGNED FOR

- ✓ FOOD PROCESSING FACILITIES/ ABATTOIRS
- ✓ MINE SITES
- ✓ HEAVY MACHINERY ENGINE BAY/ WALKWAYS & LADDERS
- ✓ HYDRAULIC SNAKE PITS
- ✓ MACHINE HOUSE LIGHTING/ OPERATOR CABIN
- ✓ HARSH UNDERGROUND LIGHTING
- ✓ DAISY CHAIN APPLICATIONS



FEATURES

- PC extrusion for max chemical resistance.
- Shatterproof - unbreakable in normal operation.
- Stainless steel ferrules and fittings for zero corrosion.
- VEET & IPART approved.
- IP69 rated for ultimate protection in cleaning regime.
- Quick-Connect fittings on both ends For simple and fast installation.

APPLICATION NOTES

- IP69 for indoor and outdoor use.
- Installation only by a licensed electrician.
- Resistant to most general chemicals and cleaners.
- Suitable for use in chiller/cold rooms down to -20°C.
- Total of 25 luminaries may be linked together on a stable 200-277V supply system.
- Interlinking Power Cable 1 meter (Part #CRS-MP-QC1FF).

TECHNICAL DRAWINGS



MODEL	A	B
	Min. mm	Ø Min. mm
CHH2250-905	470	90
CHH4550-910	940	90



CYBERLITE™

LED BATTEN SHATTERPROOF
SERIES - GEN 2 22W & 45W

MOUNTING

Easy install polished stainless steel brackets



FOOD & BEVERAGE LIGHTING

COLOUR RENDERING COMPARISON



1900K
CANDLE



2200K
HIGH PRESSURE
SODIUM LAMP



2700K-3000K
WARM WHITE
HALOGEN/
INCANDESCENT



4000K-4500K
NATURAL WHITE
METAL HALIDE



4800K
DIRECT SUN



5000K-6000K
DAY WHITE



Find out more at dura-vision.com.au or call 1800 66 55 66