

HELIOS FRAME A

HEAVY DUTY LED AC FLOOD LIGHT 400W-480W



400W MODEL

A powerful, robust, high-powered flood lighting system for large mobile plant applications. The Helios features a bespoke mounting system produced exclusively to attach directly to the M.I.D MK1763-A bracket frame. The Helios Lighting system provides the highest light output for lighting used on Drag Line & large Mining Shovel applications. Complete with multi-volt drivers rated from 200cAC to 470vAC this series works over a wide voltage range and can withstand voltage spikes. Designed and manufactured in Australia using only the highest quality components, the Helios is the most robust and heavy-duty lighting solution for tough mine plants, machinery, and structures.









PRODUCT NAME	ZONE MASTER™ HELIOS FRAME A HEAVY DUTY LED AC FLOOD LIGHT				
MODEL	400W	480W			
POWER CONSUMPTION	400W	480W			
LIGHT OUTPUT EFFECTIVE	49,658 lm at 65°C	63,840 lm at 65°C			
LED EFFICACY	124 lm/W	133 lm/W			
IP RATING	IPe	58			
OPERATING TEMP °C	-40°C to	o +70°C			
VOLTAGE RANGE	180V-52	28V/AC			
POWER FACTOR	>0.	92			
FREQUENCY RANGE	50/6	0Hz			
THERMAL MANAGEMENT	Electronic Active/Continuous				
CRI	>70 CRI				
CCT/KELVIN	3000K, 4000K, 5000K & 5700K				
BEAM TYPES	10°, 25°, 40°, 60°, 70x40° & 110°				
HOUSING	Extruded A	Aluminium			
VIBRATION RATING	15.8G	/RMS			
LINE CURRENT (230V/AC)	1.74A	2.0A			
LENS	3mm Polycarbonate				
CABLE LENGTH	Custom				
LED LIFESPAN	1 > 70,000 Hours (TA = 30°C @ L70)				
SURGE PROTECTION	10kV				
SAFETY COMPLIANCE	AS/NZS 60598.1				
WARRANTY	5 YEARS				



HELIOS FRAME A

HEAVY DUTY LED AC FLOOD LIGHT 400W-480W



480W MODEL

DESIGNED FOR


- ✓ DRAGLINES
- ✓ HYDRAULIC SHOVELS
- STACKERS / RECLAIMERS
- ✓ HEAVY INDUSTRIAL FLOOD LIGHTING

ORDERING EXAMPLE

DVZ - 400/2 - 25 - 3 - 40 - HBA - B - 1.5

MODEL WATTAGE BEAM TYPE DRIVER CCT (KELVIN) BRACKET ENCLOSURE CABLE LENGTH

MODEL	WATTAGE	BEAM TYPE	DRIVER	CCT (KELVIN)	BRACKET	ENCLOSURE	CABLE LENGTH
DVZ (ZONE MASTER)	400/2 (2x200W LAMPS)	25 (25° NARROW)	3 (200vAC-500vAC)	30 (3000K)	HBA (HELIOS FRAME A)	B (LARGE ENCLOSURE)	1.5M (STANDARD)
	480/2 (2x240W LAMPS)	40 (40° NARROW FLOOD)	2 (100vAC-270vAC)	40 (4000K)			
		60 (60° WIDE FLOOD)		50 (5000K)			
		70 x 40 (25° OVAL)		57 (5700K)			
		110 (25° ULTRA WIDE)					





HELIOS FRAME B

HEAVY DUTY LED AC FLOOD LIGHT 800W-960W



800W MODEL

A powerful, robust, high-powered flood lighting system for large mobile plant applications. The Helios features a bespoke mounting system produced exclusively to attach directly to the M.I.D MK1763-A bracket frame. The Helios Lighting system provides the highest light output for lighting used on Drag Line & large Mining Shovel applications. Complete with multi-volt drivers rated from 200cAC to 470vAC this series works over a wide voltage range and can withstand voltage spikes. Designed and manufactured in Australia using only the highest quality components, the Helios is the most robust and heavy-duty lighting solution for tough mine plants, machinery, and structures.









PRODUCT NAME	ZONE MASTER™ HELIOS FRAME B HEAVY DUTY LED AC FLOOD LIGHT				
MODEL	800W	960W			
POWER CONSUMPTION	800W	960W			
LIGHT OUTPUT EFFECTIVE	99,658 lm at 65°C	127,680 lm at 65°C			
LED EFFICACY	124.5 lm/W	133 lm/W			
IP RATING	IPé	58			
OPERATING TEMP °C	-40°C to	o +70°C			
VOLTAGE RANGE	180V-52	28V/AC			
POWER FACTOR	>0.	92			
FREQUENCY RANGE	50/6	0Hz			
THERMAL MANAGEMENT	Electronic Active/Continuous				
CRI	>70 CRI				
CCT/KELVIN	3000K, 4000K, 5000K & 5700K				
BEAM TYPES	10°, 25°, 40°, 60°, 70×40° & 110°				
HOUSING	Extruded Aluminium				
VIBRATION RATING	15.8G _/	/RMS			
LINE CURRENT (230V/AC)	1.74A 2.0A				
LENS	3mm Polycarbonate				
CABLE LENGTH	Custom				
LED LIFESPAN	1 > 70,000 Hours (TA = 30°C @ L70)				
SURGE PROTECTION	10kV				
SAFETY COMPLIANCE	AS/NZS 60598.1				
WARRANTY	5 YE	ARS			



HELIOS FRAME B

HEAVY DUTY LED AC FLOOD LIGHT 800W-960W



960W MODEL

DESIGNED FOR


- ✓ DRAGLINES
- ✓ HYDRAULIC SHOVELS
- ✓ STACKERS / RECLAIMERS
- ✓ HEAVY INDUSTRIAL FLOOD LIGHTING

ORDERING EXAMPLE

 DVZ
 800/4
 25
 3
 40
 HBB
 B
 1.5

 MODEL
 WATTAGE
 BEAM TYPE
 DRIVER
 CCT (KELVIN)
 BRACKET
 ENCLOSURE CABLE LENGTH

MODEL	WATTAGE	BEAM TYPE	DRIVER	CCT (KELVIN)	BRACKET	ENCLOSURE	CABLE LENGTH
DVZ (ZONE MASTER)	800/4 (4x200W LAMPS)	25 (25° NARROW)	3 (200vAC-500vAC)	30 (3000K)	HBB (HELIOS FRAME B)	B (LARGE ENCLOSURE)	1.5 (1.5M CABLE)
	960/4 (4x240W LAMPS)	40 (40° NARROW FLOOD)	2 (100vAC-270vAC)	40 (4000K)			
		60 (60° WIDE FLOOD)		50 (5000K)			
		70 x 40 (25° OVAL)		57 (5700K)			
		110 (25° ULTRA WIDE)					





HELIOS FRAME C

HEAVY DUTY LED AC FLOOD LIGHT 800W-960W



A powerful, robust, high-powered flood lighting system for large mobile plant applications. The Helios features a bespoke mounting system produced exclusively to attach directly to the M.I.D MK1763-A bracket frame. The Helios Lighting system provides the highest light output for lighting used on Drag Line & large Mining Shovel applications. Complete with multi-volt drivers rated from 200cAC to 470vAC this series works over a wide voltage range and can withstand voltage spikes. Designed and manufactured in Australia using only the highest quality components, the Helios is the most robust and heavy-duty lighting solution for tough mine plants, machinery, and structures.









PRODUCT NAME	ZONE MASTER™ HELIOS FRAME C HEAVY DUTY LED AC FLOOD LIGHT				
MODEL	800W	960W			
POWER CONSUMPTION	800W	960W			
LIGHT OUTPUT EFFECTIVE	99,658 lm at 65°C	127,680 lm at 65°C			
LED EFFICACY	124.5 lm/W	133 lm/W			
IP RATING	IPo	58			
OPERATING TEMP °C	-40°C to	o +70°C			
VOLTAGE RANGE	180V-52	28V/AC			
POWER FACTOR	>0.	92			
FREQUENCY RANGE	50/6	OHz			
THERMAL MANAGEMENT	Electronic Active/Continuous				
CRI	>70 CRI				
CCT/KELVIN	3000K, 4000K, 5000K & 5700K				
BEAM TYPES	10°, 25°, 40°, 60°, 70x40° & 110°				
HOUSING	Extruded A	Aluminium			
VIBRATION RATING	15.8G	/RMS			
LINE CURRENT (230V/AC)	1.74A	2.0A			
LENS	3mm Polycarbonate				
CABLE LENGTH	Custom				
LED LIFESPAN	1 > 70,000 Hours (TA = 30°C @ L70)				
SURGE PROTECTION	10kV				
SAFETY COMPLIANCE	AS/NZS 60598.1				
WARRANTY	5 YEARS				



HELIOS FRAME C

HEAVY DUTY LED AC FLOOD LIGHT 800W-960W




DESIGNED FOR

- ✓ DRAGLINES
- ✓ HYDRAULIC SHOVELS
- STACKERS / RECLAIMERS
- ✓ HEAVY INDUSTRIAL FLOOD LIGHTING

ORDERING EXAMPLE

DVZ - 800/4 -25 40 **HBC** 1.5 В MODEL WATTAGE **BEAM** DRIVER CCT (KELVIN) BRACKET **ENCLOSURE CABLE TYPE LENGTH**

MODEL	WATTAGE	BEAM TYPE	DRIVER	CCT (KELVIN)	BRACKET	ENCLOSURE	CABLE LENGTH
DVZ (ZONE MASTER)	800/4 (4x200W LAMPS)	25 (25° NARROW)	3 (200vAC-500vAC)	30 (3000K)	HBC (HELIOS FRAME C)	B (LARGE ENCLOSURE)	1.5 (1.5M CABLE)
	960/4 (4x240W LAMPS)	40 (40° NARROW FLOOD)	2 (100vAC-270vAC)	40 (4000K)			
		60 (60° WIDE FLOOD)		50 (5000K)			
		70 x 40 (25° OVAL)		57 (5700K)			
		110 (25° ULTRA WIDE)					





ZONE MASTERTM

HELIOS FRAME D

HEAVY DUTY LED AC FLOOD LIGHT 800W-960W



A powerful, robust, high-powered flood lighting system for large mobile plant applications. The Helios Lighting system provides the highest light output for lighting used on Drag Line & large Mining Shovel applications. Complete with multi-volt drivers rated from 200cAC to 470vAC this series works over a wide voltage range and can withstand voltage spikes. Designed and manufactured in Australia using only the highest quality components, the Helios is the most robust and heavy-duty lighting solution for tough mine plants, machinery, and structures.









PRODUCT NAME	ZONE MASTER™ HELIOS FRAME D HEAVY DUTY LED AC FLOOD LIGHT				
MODEL	800W 960W				
POWER CONSUMPTION	400W	480W			
LIGHT OUTPUT EFFECTIVE	99,658 lm at 65°C	127,680 lm at 65°C			
LED EFFICACY	124.5 lm/W	133 lm/W			
IP RATING	IPé	58			
OPERATING TEMP °C	-40°C to	o +70°C			
VOLTAGE RANGE	180V-52	28V/AC			
POWER FACTOR	>0.	92			
FREQUENCY RANGE	50/6	OHz			
THERMAL MANAGEMENT	Electronic Active/Continuous				
CRI	>70 CRI				
CCT/KELVIN	3000K, 4000K, 5000K & 5700K				
BEAM TYPES	10°, 25°, 40°, 60°, 70x40° & 110°				
HOUSING	Extruded Aluminium				
VIBRATION RATING	15.8G,	/RMS			
LINE CURRENT (230V/AC)	1.74A 2.0A				
LENS	3mm Polycarbonate				
CABLE LENGTH	Custom				
LED LIFESPAN	1 > 70,000 Hours (TA = 30°C @ L70)				
SURGE PROTECTION	10kV				
SAFETY COMPLIANCE	AS/NZS 60598.1				
WARRANTY	5 YE	ARS			



HELIOS FRAME D

HEAVY DUTY LED AC FLOOD LIGHT 800W-960W



DESIGNED FOR

- ✓ DRAGLINES
- ✓ HYDRAULIC SHOVELS
- STACKERS / RECLAIMERS
- ✓ HEAVY INDUSTRIAL FLOOD LIGHTING

ORDERING EXAMPLE

DVZ - 800/2 -25 40 **HBD** 1.5 C WATTAGE **BEAM** DRIVER CCT (KELVIN) BRACKET **ENCLOSURE CABLE** MODEL **LENGTH**

MODEL	WATTAGE	BEAM TYPE	DRIVER	CCT (KELVIN)	BRACKET	ENCLOSURE	CABLE LENGTH
DVZ (ZONE MASTER)	800/2 (2x400W LAMPS)	25 (25° NARROW)	3 (200vAC-500vAC)	30 (3000K)	HBD (HELIOS FRAME D)	C (SLOPE ROOF ENCLOSURE)	1.5 (1.5M CABLE)
	960/2 (2x480W LAMPS)	40 (40° NARROW FLOOD)	2 (100vAC-270vAC)	40 (4000K)			
		60 (60° WIDE FLOOD)		50 (5000K)			
		70 x 40 (25° OVAL)		57 (5700K)			
		110 (25° ULTRA WIDE)					

